

Choose your actuator:

1. Model:

- ☐ easyE-35
- ☐ easyE-50
- ☐ easyE-60

2. Stroke length:

- ☐ 50, 100, 150, 200, 250, 300, 350, 400, 500 and 750mm (others on request)

3. Gear ratio:

- ☐ C, D, E, F, G, H (speed and load see table)

4. Voltage:

- ☐ 12V DC (only easyE-35 and easyE-50)
- ☐ 24V DC
- ☐ 24V EN/UL 60.601

5. Temperature:

- ☐ standard (-5°C - +70°C)
- ☐ low (-40°C - +70°C)
- ☐ high (-5°C - +90°C)

6. Cable length:

- ☐ 1m - 9m (others on request)

7. Connector:

- ☐ no connector
- ☐ Molex minifit

8. Material:

- ☐ Standard steel
- ☐ AISI 316

9. Protection class:

- ☐ IP66 (standard)
- ☐ IP68
- ☐ IP69K
- ☐ ATEX zone 22, group II 3D compliant

9. Certification (only easyE-35 and easyE-50):

- ☐ EN/UL/CSA 60.601 (only 24 V DC)

10. Hall sensor:

- ☐ no (standard)
- ☐ yes (cable will change)

11. Low noise:

- ☐ no (standard)
- ☐ yes (no stainless steel)

12. Color:

- ☐ Black (standard)
Available in all RAL colors

13. Connecting parts

